

TOP QUALITY GREASE FOR VERY HIGH-PRESSURE APPLICATIONS **EP3**

NTN  **SNR**


www.ntn-snr.com



With You



HEAVY DUTY EP3



Top quality grease for very high pressure applications such as in the heavy industry: metallurgy, construction, transport, etc.

STANDARD APPLICATIONS

Conveyors, lifting devices, truck wheel hubs, high powered electric motors, water pumps, presses, etc.

BENEFITS

Excellent performance under heavy loads and high speeds. Good properties in the presence of water, excellent protection against wear and corrosion.

TEMPERATURE RANGE

from -25°C to +140°C

Lubricants: description	HEAVY DUTY
NLGI consistency grade	3
Base oil	Mineral
Thickener / type of soap	Lithium with EP additives
Colour	Amber
Base oil viscosity (cSt) - at 40°C	115
- at 100°C	11
Service temperature range (°C)	From -25 to +140
Drop point (°C) DIN ISO2176	> 190
Suitable for medium loads P<C/5	++
Suitable for high loads P<C/5	++
Suitable for low speeds n.Dm <100,000	+
Suitable for high speeds n.Dm >100,000	+
Properties in humid environments, in the presence of water	++
Suitable for low-amplitude oscillations	+
Suitable for vibrations when shutdown	-
Adhesion	+
Low torque	+
Low noise levels	+
Anti-corrosion protection	++
Resistance to chemical agents	-
Pumpability	++
Sizes available	1 kg can
Remarks	Previous name: EP

ALSO AVAILABLE IN OUR RANGE...



READY BOOSTER

- 60 cm³ and 125 cm³
- Low-cost
- Robust
- Ergonomic: excellent grease level visibility
- Can be used in explosive areas



SMART BOOSTER

- + capacity: 125 cm³
- Precise, ergonomic
- Adjustable discharge (in months) using an LCD
- Constant flow, regardless of ambient temperature
- Recyclable: re-usable control unit
- Suitable for explosive areas



DRIVE BOOSTER

- Polyvalent
- 2 sizes: 120 cm³ and 250 cm³
- Multi-purpose
- Precise
- Powerful: suitable for remote lubrication
- Rechargeable

POLIPUMP:

Low-cost and easy to implement centralised greasing

Cost-effective multipoint greasing solution, efficient and easy to set up, allowing the lubrication of 1 to 35 points.



Distributed by:



mineral circles bearings
Tel: +971 4 886 5100
Fax: +971 4 886 5123
E-mail: export@mcb.ae

This document is the exclusive property of NTN-SNR ROULEMENTS. Any total or partial reproduction hereof without the prior consent of NTN-SNR ROULEMENTS is strictly prohibited. Legal action may be brought against anyone breaching the terms of this paragraph.

NTN-SNR ROULEMENTS shall not be held liable for any errors or omissions that may have crept into this document despite the care taken in drafting it. Due to our policy of continuous research and development, we reserve the right to make changes without notice to all or part of the products and specifications mentioned in this document.

© NTN-SNR ROULEMENTS, international copyright 2017.

